

WLO-101-MODELOS E y O



Módelo E



Módelo O



| CÓDIGO | W | Lm | KELVIN GRADE |
|--------------------|-------|-------|--------------|
| WLO-101-HFIL135E5K | 135 w | 9500 | 5000 |
| WLO-101-HFIL135O5K | 135 w | 9500 | 5000 |
| WLO-101-HFIL150E5K | 150 w | 9500 | 5000 |
| WLO-101-HFIL150O5K | 150 w | 9500 | 5000 |
| WLO-101-HFIL165E5K | 165 w | 11600 | 5000 |
| WLO-101-HFIL200E5K | 200 w | 14000 | 5000 |
| WLO-101-HFIL4005K | 40 w | 1400 | 5000 |
| WLO-101-HFIL65E5K | 65 w | 4200 | 5000 |
| WLO-101-HFIL85E5K | 85 w | 6000 | 5000 |

| Efficacy (lm/W) | RA | Colour temperature (K) | Start time (s) | Lumen depression at 20000H |
|-----------------|-----|------------------------|----------------|----------------------------|
| 60~65 | ≥80 | | ≤0.5 | ≥80% |
| 60~65 | ≥80 | 2700K ~ 6500K | ≤0.5 | ≥80% |
| 65~70 | ≥80 | | ≤0.5 | ≥80% |
| 65~70 | ≥75 | | ≤0.5 | ≥80% |
| 65~70 | ≥75 | | ≤0.5 | ≥80% |
| 65~70 | ≥75 | | ≤0.5 | ≥80% |
| 65~70 | ≥75 | 3000K ~ 6500K | ≤0.5 | ≥80% |
| 65~70 | ≥75 | | ≤0.5 | ≥80% |
| 65~70 | ≥75 | | ≤0.5 | ≥80% |
| 65~70 | ≥75 | | ≤0.5 | ≥80% |

| Power (W) | Input voltages (V) | Input Current (A) | Operation frequency (MHz) | Power factor | Environment temperature (°C) | EMC | Dimension of bulb (mm) | | | | Life × (H) |
|-----------|--------------------|-------------------|---------------------------|--------------|------------------------------|--|------------------------|-----|--------------|--------|------------|
| | | | | | | | Diameter | | Whole length | | |
| | | | | | | | P | E | P | E | |
| 40 | AC 110/220 | 0.4/0.2 | 2.65 | >0.95 | -30~+50 | EN55015:2006+A1:2007 EN61000-3-2:2006 EN61000-3-3:2008 EN61547:1995+A1:2000 | - | 90 | - | 193 | 60,000 |
| | DC 12/24 | 3.4/1.7 | 2.65 | - | | | - | 90 | - | 193 | |
| 50 | AC 110/220 | 0.5/0.25 | 2.65 | >0.95 | -30~+50 | | - | 90 | - | 193 | 60,000 |
| | DC 12/24 | 4.2/2.1 | 2.65 | - | | | - | 90 | - | 193 | |
| 65 | AC 110/220 | 0.6/0.3 | 2.65 | >0.95 | -30~+50 | | 110 | 90 | 185 | 193 | 60,000 |
| | DC 12/24 | 5.6/2.8 | 2.65 | - | | | 110 | 90 | 185 | 193 | |
| 85 | AC 110/220 | 0.8/0.4 | 2.65 | >0.95 | -30~+50 | | 130 | 120 | 210 | 238 | 60,000 |
| 100 | AC 110/220 | 1.0/0.5 | 2.65 | >0.98 | -30~+50 | | 130 | 120 | 210 | 238 | 60,000 |
| 120 | AC 110/220 | 1.1/0.55 | 2.65 | >0.98 | -30~+50 | | 130 | 120 | 210 | 238 | 60,000 |
| 135 | AC 110/220 | 1.2/0.6 | 2.65 | >0.98 | -30~+50 | | 130 | 120 | 210 | 238 | 60,000 |
| 150 | AC 110/220 | 1.4/0.7 | 2.65 | >0.98 | -30~+50 | 130 | 120 | 210 | 238 | 60,000 | |
| 165 | AC 220 | 1.6/0.8 | 2.65 | >0.98 | -30~+50 | 130 | - | 210 | - | 60,000 | |
| 200 | AC 220 | 2.0/1.0 | 2.65 | >0.98 | -30~+50 | 150 | - | 238 | - | 60,000 | |